

Steps for Assembling the Portable American Flag

- Each flag kit will contain the following components: one small American flag (attached to a pole section); one black flag stand; two additional gold-colored pole sections; one hex key wrench; one silver 2-inch insert for the base; one black $\frac{1}{4}$ inch screw; one gold-colored "Acorn Cap;" and two flag pole rings.
- To assemble the flag, follow these steps:
 1. Remove the black 2-part flag stand from the carrying case.
 2. Assemble the 2 parts forming a "T" shape. (The longer piece will be the bottom part of the "T" shape).
 3. Locate the black $\frac{1}{4}$ inch screw, and the silver 2-inch round insert.
 4. Place the 2-inch round insert on top of the round center hole of the flag stand.
 5. Insert the black $\frac{1}{4}$ inch screw through the center hole and into the bottom of the silver 2-inch round insert and tighten. (Use both hands.)
 6. Place the assembled stand on a flat surface with the insert completely vertical (pointing straight up).
 7. Remove the flag pole pieces from the carrying case. (Note: The flag should already be attached to one pole section).
 8. Insert the flagpole pieces into one another. (Note: One end of the flag pole will be smaller and should be the bottom).
 9. Locate the gold "Acorn Cap" from the carrying case and attach it to the top end of the assembled pole.
 10. Slide the assembled American flag onto the 2-inch round insert.

The flag is now assembled and ready for display.